



SERIES LN4S

Power Flame 30 PPM ^[1] Low Nox Burner Information

Boiler Size	Burner Model	Motor Horsepower ^[2]			Firing Sequence	Standard Flame Safeguard	Gas Train			FGR Line Size
	Gas and Gas/#2 Oil	Blower	Oil Pump	A/C	Gas and Gas/#2 Oil		Minimum Gas Pressure	Maximum Gas Pressure	Size	
LN4S-100	LNIC4-G(O)-25	3	1/2	N/A	Full Mod	RM7840L/UV	7.3" w.c.	14" w.c.	2"	8"
LN4S-125	LNIC4-G(O)-30	5	1/2	N/A	Full Mod	RM7840L/UV	9.9" w.c.	28" w.c.	2-1/2"	8"
LN4S-150	LNIC5-G(O)-30	7 1/2	1/2	N/A	Full Mod	RM7840L/UV	13.2" w.c.	28" w.c.	2-1/2"	8"
LN4S-175	LNIC6-G(O)-30	10	1/2	N/A	Full Mod	RM7840L/UV	9.9" w.c.	28" w.c.	3"	10"
LN4S-200	LNIC6-G(O)-30	10	1/2	N/A	Full Mod	RM7840L/UV	12.8" w.c.	28" w.c.	3"	10"
LN4S-250	LNICM9A-G(O)-30	5	1/2	5	Full Mod	RM7840L/UV	25.7" w.c.	10 psig	3"	10"
LN4S-300	LNICM9B-G(O)-30	5	1/2	5	Full Mod	RM7840L/UV	32.7" w.c.	10 psig	3"	10"
LN4S-350	LNICM9B-G(O)-30	7 1/2	1/2	5	Full Mod	RM7840L/UV	40.9" w.c.	10 psig	3"	12"
LN4S-400	LNICM10-G(O)-30	10	3/4	5	Full Mod	RM7840L/UV	63.0" w.c.	10 psig	3"	12"
LN4S-500	LNICM10B-G(O)-30	15	3/4	7 1/2	Full Mod	RM7840L/UV	91.0" w.c.	10 psig	3"	12"
LN4S-600	LNICM11-G(O)-30	20	3/4	7 1/2	Full Mod	RM7840L/UV	90.0" w.c.	10 psig	3"	16"
LN4S-700	LNICM11-G(O)-30	20	3/4	7 1/2	Full Mod	RM7840L/UV	94.0" w.c.	10 psig	3"/4" (1)	16"
LN4S-800	LNICM11A-G(O)-30	25	2	15	Full Mod	RM7840L/UV	74.8" w.c.	10 psig	3"HF	16"

Gas and Gas/#2 Oil Firing Sequence

ALL MODELS: FULL MODULATION WITH PROVEN LOW FIRE START, SYNCHRONIZED FUEL/AIR CONTROL WITH MODULATING MOTOR.

NOTES:

^[1] EXPECTED EMISSIONS ARE 30 PPMVD OR LESS NO_x (CORRECTED TO 3.0% O₂) AND 400 PPMVD OR LESS CO (CORRECTED TO 3.0% O₂) WHEN FIRING NATURAL GAS

^[2] ALL BLOWER AND AIR COMPRESSOR MOTORS AVAILABLE 208-230-460/60/3, INDICATE JOBSITE ON ORDER. OIL PUMP MOTORS ARE 230/60/1; CONSULT FACTORY FOR OTHER VOLTAGES

^[3] DUAL SIZE GAS TRAINS: LEAK TEST COCK, MAIN GAS VALVE AND AUXILIARY GAS VALVE ARE INDICATED BY THE FIRST NUMBER. GAS REGULATOR AND MAIN SHUTOFF COCK ARE INDICATED BY THE SECOND NUMBER.



SERIES LN4S

Burner Equipment

Equipment	Fuel	Description
Control Cabinet	Gas, Gas/#2 Oil	NEMA 1A with hinged door
Control Voltage Transformer	Gas, Gas/#2 Oil	Included
Motor Starter	Gas, Gas/#2 Oil	Magnetic starter with overload protection
Fusing	Gas, Gas/#2 Oil	Control circuit only
Ignition	Gas, Gas/#2 Oil	Gas/Electric pilot
Signal Lights	Gas, Gas/#2 Oil	(4) - power on, fuel valve open, call for heat, flame failure
Air Flow Safety Switch	Gas, Gas/#2 Oil	All Models
Gas Train	Gas, Gas/#2 Oil	UL gas train for minimum inlet pressure indicated on Burner Information table. Assembled, wired and mounted on unit consisting of the following: Manual shut off valve Gas pressure Regulator Manual leak test valve 100 & 125: Single Motorized Gas Valve with Proof of closure 150 & Larger: 2 Gas Valves Main Gas Valve: Motorized type Auxillary gas valve: Solenoid type High and Low gas pressure switches
Oil Pump	Gas/#2 Oil	Remote oil pump set with motor and accessories mounted on boiler skid
Oil Firing Type	Gas/#2 Oil	100 - 200: Pressure Atomizing 250 and larger: Air Atomizing
Pilot Gas Controls	Gas, Gas/#2 Oil	All models have gas/electric pilot, manual pilot shut-off valve, pilot gas pressure regulator and solenoid gas valve
Fuel Changeover	Gas/#2 Oil	Manual switch
Flue Gas Recirculation	Gas, Gas/#2 Oil	Induced flue gas recirculation, no external fan is required