


# HYDRONIC CAST IRON HEAT OIL, GAS OR COMBINATION

**Burnham**<sup>®</sup>  
AMERICA'S BOILER COMPANY

**PF-5 SERIES** 

Heating Capacities:  
620 to 3430 MBH



# PF-5 SERIES HOT WATER OR STEAM BOILER

Maximum Water Working Pressure: 70 PSI-Water ; 15 PSI-Steam

## The finest in large cast iron boiler design.

Utilizing a completely sealed, forced draft wet base design, the Burnham® PF-5 Series requires no separate base or combustion chamber. The sealed, forced draft design provides optimum draft for controlled combustion, eliminating the need for high chimneys or mechanical equipment to artificially induce proper draft.

The sectional construction of the PF-5 Series makes it ideal for use in installations where the boiler room is not easily accessible due to structural limitations. In addition to being shipped as individual sections the boiler is available with factory-assembled sections or as a completely packaged unit. The packaged unit is fastened to a steel skid to facilitate lifting with a fork truck or crane. The skid can serve as the boiler foundation, replacing the need for a concrete pad. A factory fire-test is available on all packaged units.

Available in eighteen sizes starting at Gross Outputs of 620 MBH, the PF-5 Series fires gas, oil or gas/oil combination and can be equipped with either steam or water trim and controls.

The product is energy efficient with a combustion efficiency of up to 82%. All sizes exceed the efficiency requirements of ASHRAE 90.1.

### Quality breeds Security

Each PF-5 boiler section is hydrostatically tested at two and one half times rated working pressure to make sure that the section is flawless. Factory-assembled sections are tested at one and one half times the rated working pressure. The sections are

surface ground to insure smooth surface mating, and sealed gas-tight with an elastic sealing compound. This sealant is used on all section joints to guarantee a completely sealed and gas-tight assembly required for forced draft operation. The sealant is easily applied and takes less time than applying conventional gasket materials and lasts many times longer.

Each section is then joined with quality cast iron nipples which will



increase the longevity of the boiler by resisting petroleum based chemicals, including antifreeze

which can deteriorate the gaskets used in some competitor's boilers. Time-proven cast iron nipples last the life of the boiler. They expand and contract along with the sections they join ensuring the integrity of the entire section assembly.

### Thermal Pump—Making Waves

Incorporated into the wet base design is a "thermal pump" action that greatly improves circulation in both water and steam versions of the PF-5 Series. This thermal pump insures good steam quality as well as maximum tankless heater capacity. The thermal pumping action is created by causing greater heat transfer on one side of the boiler than on the other. An upward flow of water occurs on the side where heat transfer is greatest, and a downward water flow results on the side where heat transfer is lowest. Continuous water circulation is assured.




Diagram of thermal pump action

Added safety and system longevity are achieved with the addition of a pressure relief door as standard equipment. This will reduce potential damage to the breeching or heat exchanger in the event of an inadvertent delayed ignition of the burner.

### The "Smart" Choice


Specifying a heating system in CSI (Construction Specifications Institute) format is made easy with Burnham's Smartspec computer software program. Use the program menu to specify atmospheric or forced draft; steam or hot water; gas, oil, or combination fuels; single or lead-lag; knockdown or packaged; and output ratings in gross, net or square feet of steam. Optional equipment menu and built-in editing features let you create a customized CSI specification. Consult your local Burnham sales representative for details.

### Burnham—The name for quality

Burnham has earned a reputation for quality and dependability going back to 1856. To ensure quality and availability, castings for the PF-5 and all other boilers are produced at its in-house modern foundry, a claim no other boiler manufacturer can make. Look to Burnham, the name in quality boilers.



# PF-5 FEATURES AND STANDARD EQUIPMENT



## Standard equipment.

ALL BOILERS—Sections unassembled  
 • Flush insulated jacket • Burner mounting plate (priced separately) • Pressure relief door • Fire wall plates • Flue damper assembly • Flue canopy • Trim • Miscellaneous plugs, bushings and fittings.

STEAM TRIM—ASME Safety valve • PA-404A Pressuretrol • Gauge glass assembly • Boiler drain cock • Pressure vacuum gauge.

WATER TRIM—ASME Safety relief valve • L-4006A High limit • Pressure temperature gauge • Boiler drain cock.  
 OIL BOILERS—Flange mounted flame retention oil burner furnished with 2 stage fuel unit, primary control and dual oil valve.

GAS BOILERS—Flange mounted gas burner with standard controls meeting the latest UL requirements • Dual gas valves • gas-electric ignition with proven gas pilot • ultra-violet flame detector • Electronic programming controls and components are factory wired in a burner mounted control cabinet.


GAS/OIL BOILERS—Flange mounted combination gas/oil burner with standard controls meeting latest UL requirements • Manually operated fuel transfer switch for dual fuel changeover • Dual gas valves and oil valves • Electric ignition with proven gas pilot on the gas side; direct spark ignition on the oil side • Ultra-violet flame detector • Electronic programming controls and components are factory wired in a burner mounted control cabinet (includes high limit with manual reset and a probe low water cutoff).

## Optional equipment


Assembled sections • Completely packaged • Packaged and fire-tested • Tankless heaters • 30 PSI and 70 PSI ASME safety relief valves • Combustion and hydronic controls to meet special applications including F.M., I.R.I. and ASME CSD-1.

# DIMENSIONS (in inches)

Boiler Number	Number of Sections	A	B	C	Burner Dimension D					L Flush Jacket	Assembled Section Weight Lbs.	Approximate Shipping Weight Lbs.
					Powerflame—C			Beckett	Carlin	G&P	Webster	
					Gas	Oil	Gas/Oil	C F		R	JB	
PF-504	4	10	12	19½	29	29	34	12	17	26	25	1975
PF-505	5	10	12	25½	29	29	34	23	22	26	25	2330
PF-506	6	10	12	31½	29	29	34	23	22	26	25	2705
PF-507	7	10	12	37½	34	34	34	23	22	26	25	3050
PF-508	8	10	12	43½	34	34	34	24	22	26	25	3430
PF-509	9	14	12	49½	34	34	34	24	22	26	25	3775
PF-510	10	14	12	55½	34	34	34	24	22	26	25	4175
PF-511	11	14	12	61½	34	34	34	24	22	29	25	4610
PF-512	12	14	27	67½	34	34	34	24	22	29	25	4985
PF-513	13	14	33	73½	34	34	34	25	22	29	25	5330
PF-514	14	14	39	79½	34	34	34	25	29	29	29	5720
PF-515	15	14	45	85½	34	34	34	25	29	29	29	6055
PF-516	16	18	51	91½	39	39	39	25	29	29	29	6405
PF-517	17	18	57	97½	39	39	39	26	30	29	29	6745
PF-518	18	18	63	103½	39	39	39	26	30	29	29	7110
PF-519	19	18	69	109½	39	39	39	26	30	29	29	7420
PF-520	20	18	75	115½	39	39	39	—	30	29	29	7880
PF-521	21	18	81	121½	39	39	39	—	30	29	29	8235



## RECOMMENDED SLING ARRANGEMENT



### NOTES:

1. This boiler can be lifted by fork truck. Do not truck from front.
2. When lifting from rear, forks must extend beyond center of gravity and second skid gross bar.
3. When lifting from side, forks must extend to opposite skid rail and straddle center of gravity.
4. Cable spreader is to prevent jacket damage. Spreader should be B (width of skid) + 12". Adjust cable lengths to lift at approx. center of gravity per chart.

## DIMENSIONS

Boiler Model	Number of Sections	Length A	Width B	Height C	Approximate Center of Gravity D*	Approx. Shipping Wt. (lbs)
PF-504	4	70	44	65¼	21½	2322
PF-505	5	76	44	65¼	24½	2694
PF-506	6	82	44	65¼	27½	3087
PF-507	7	88	44	65¼	31½	3450
PF-508	8	94	44	65¼	34½	3879
PF-509	9	100	44	65¼	37½	4242
PF-510	10	112	44	65¼	40½	4709
PF-511	11	118	44	65¼	43½	5171
PF-512	12	124	44	65¼	46½	5586
PF-513	13	130	44	65¼	49½	5982
PF-514	14	136	44	65¼	52½	6392
PF-515	15	142	44	65¼	55½	6748
PF-516	16	148	44½	67¼	58½	7178
PF-517	17	154	44½	67¼	61½	7539
PF-518	18	160	44½	67¼	65½	7974
PF-519	19	166	44½	67¼	68½	8305
PF-520	20	172	44½	67¼	71½	8785
PF-521	21	178	44½	67¼	74½	9161


\*Varies slightly with burner and gas train configuration.



### TANKLESS HEATER RATINGS\* (Water and Steam)

Boiler Number	Number of #548 Tankless Heaters Installed*							
	1	2	3	4	5	6	7	8
PF-504	8.0							
PF-505	8.0	16.0						
PF-506	8.0	16.0						
PF-507	8.0	16.0	24.0					
PF-508	8.0	16.0	24.0					
PF-509	8.0	16.0	24.0	32.0				
PF-510	8.0	16.0	24.0	32.0				
PF-511	8.0	16.0	24.0	32.0				
PF-512	8.0	16.0	24.0	32.0	40.0			
PF-513	8.0	16.0	24.0	32.0	40.0			
PF-514	8.0	16.0	24.0	32.0	40.0			
PF-515	8.0	16.0	24.0	32.0	40.0	48.0		
PF-516	8.0	16.0	24.0	32.0	40.0	48.0		
PF-517	8.0	16.0	24.0	32.0	40.0	48.0		
PF-518	8.0	16.0	24.0	32.0	40.0	48.0	56.0	
PF-519	8.0	16.0	24.0	32.0	40.0	48.0	56.0	
PF-520	8.0	16.0	24.0	32.0	40.0	48.0	56.0	64.0
PF-521	8.0	16.0	24.0	32.0	40.0	48.0	56.0	64.0


\*Ratings are given in gallons per minute continuous draw of water heated from 40°F to 140°F with 200°F boiler water.



### CONTROL TAPPINGS


Location	Size of Tappings	Steam	Water
A	3	Low water cut-off	Not used
B	3/4	Pressure limit control	Temperature limit control
C	3/4	Operating cont. Tankless heater	Operating cont. Tankless heater
D	1/2	Pressure gauge	Pressure Temperature Gauge
E	3/4	Not used	Not used
F	3/4	Not used	Reverse acting control
G	1/2	Gauge glass	Not used
H	1	Water Feeder, LWCO, Water Column	Not used
I	3/4	Probe Type Low Water Cutoff	Not Used

NOTE—3" blow-off on back section safety or relief valve piped in connection with blow-off.




### BURNER MOUNTING PLATES

(8 1/2" diameter mounting plate is standard except as shown below.)



#### GORDON & PIATT

Boiler Number	D
PF-507-512	8 1/2"
PF-513-521	10 1/2"



#### CARLIN

Boiler Number	D
PF-514-516	8 7/8"
PF-517-521	10 7/8"

#### POWER FLAME

Boiler Number	D
PF-507-515	9"
PF-516-521	10 3/8"


#### WEBSTER

Boiler Number	D
PF-504-513	7 1/4"
PF-514-521	9 1/4"


# MINIMUM PIPING RECOMMENDATIONS

## WATER BOILER


Boiler Number	Supply and Return (Inches)
PF-504-505	2½
PF-506-507	3
PF-508-513	4
PF-514-521	5



PF-504 thru PF-507




PF-508 thru PF-513




PF-514 thru PF-521

## Steam Boiler


Boiler Number	Pipe Size (inches)			
	Riser	Return	Header	Equalizer
PF-504	(1) 4	2	4	2½
PF-505	(1) 4	2	4	2½
PF-506	(2) 4	2½	6	2½
PF-507	(2) 4	2½	6	2½
PF-508	(2) 4	2½	6	2½
PF-509	(2) 4	2½	6	2½
PF-510	(3) 4	2½	8	2½
PF-511	(3) 4	3	8	4
PF-512	(3) 4	3	8	4
PF-513	(3) 4	3	8	4
PF-514	(4) 4	3	8	4
PF-515	(4) 4	3	8	4
PF-516	(4) 4	3	8	4
PF-517	(4) 4	3	8	4
PF-518	(5) 4	3	8	4
PF-519	(5) 4	3	8	4
PF-520	(5) 4	3	8	4
PF-521	(5) 4	3	10	4




PF-504 and PF-505




PF-506 thru PF-509



PF-510 thru PF-513



PF-514 thru PF-517



PF-518 thru PF-521



# BURNER SCHEDULES

## OIL BURNERS

Boiler Number	Beckett			Carlin		Gordon-Platt		Power-Flame		Webster	
	Burner Number	Standard Motor Voltage		Burner Number	Standard Motor Voltage	Burner Number	Standard Motor Voltage	Burner Number	Standard Motor Voltage	Burner Number	Standard Voltage
PF-504	CF800	120/60/1		301CRD	120/60/1	R6 2-0	120/60/1	C1-OS	120/60/1	JB10-03	120/60/1
PF-505	CF1400	120/60/1		701CRD	120/60/1	R6 2-0	120/60/1	C1-OS	120/60/1	JB10-03	120/60/1
PF-506	CF1400	120/60/1		701CRD	120/60/1	R6 2-0	120/60/1	C1-OS	120/60/1	JB10-03	120/60/1
PF-507	CF1400	120/60/1		701CRD	120/60/1	R8-0	120/60/1	C2-OAS	240/60/1	JB10-03	120/60/1
PF-508	CF2300	120/60/1		701CRD	120/60/1	R8-0	120/60/1	C2-OAS	240/60/1	JB10-03	120/60/1
PF-509	CF2300	120/60/1		801CRD	230/60/1	R8-0	120/60/1	C2-OAS	240/60/1	JB10-07	120/60/1
PF-510	CF2300	120/60/1		801CRD	230/60/1	R8.1-0	240/60/1	C2-DBS	240/60/1	JB10-07	120/60/1
PF-511	CF2300	120/60/1		801CRD	230/60/1	R8.2-0	240/60/1	C2-DBS	240/60/1	JB10-07	120/60/1
PF-512	CF2300	120/60/1		801CRD	230/60/1	R8.3-0	240/60/3	C2-DBS	240/60/1	JB10-07	120/60/1
PF-513	CF2500	230/60/1		801CRD	230/60/1	R10 9-0	240/60/3	C2-DBS	240/60/1	JB10-07	120/60/1
PF-514	CF2500	230/60/1		1050FFD	230/60/3	R10 9-0	240/60/3	C2-DBS	240/60/3	JB20-10	240/60/3
PF-515	CF2500	230/60/1		1050FFD	230/60/3	R10 9-0	240/60/3	C2-DBS	240/60/3	JB20-10	240/60/3
PF-516	CF2500	230/60/1		1050FFD	230/60/3	R10-0	240/60/3	C3-0	240/60/3	JB20-10	240/60/3
PF-517	CF3500	230/60/1		1150FFD	230/60/3	R10-0	240/60/3	C3-0	240/60/3	JB20-10	240/60/3
PF-518	CF3500	230/60/1		1150FFD	230/60/3	R10.1-0	240/60/3	C3-0	240/60/3	JB20-10	240/60/3
PF-519	CF3500	230/60/1		1150FFD	230/60/3	R10.1-0	240/60/3	C3-0	240/60/3	JB20-20	240/60/3
PF-520	CF3500	230/60/1		1150FFD	230/60/3	R10.1-0	240/60/3	C3-0	240/60/3	JB20-20	240/60/3
PF-521	CF3500	230/60/1		1150FFD	230/60/3	R10.1-0	240/60/3	C3-0	240/60/3	JB20-20	240/60/3

## GAS BURNERS\*

Boiler Number	Gordon-Platt			Power Flame			Webster		
	Burner Number	Min. Gas Press. Req'd. In. W.C.	Standard Motor Voltage	Burner Number	Min. Gas Press. Req'd. In. W.C.	Standard Motor Voltage	Burner Number	Min. Gas Press. Req'd. In. W.C.	Standard Voltage
PF-504	R6 2-G	6.7	120/60/1	C1-G-12	5.0	120/60/1	JB1G-03	4.0	120/60/1
PF-505	R6 2-G	5.9	120/60/1	C1-G-12	5.9	120/60/1	JB1G-03	6.1	120/60/1
PF-506	R6 2-G	6.3	120/60/1	C1-G-12	6.8	120/60/1	JB1G-03	5.0	120/60/1
PF-507	R8-G	6.4	120/60/2	C2-G-15	8.1	120/60/1	JB1G-03	6.8	120/60/1
PF-508	R8-G	6.1	120/60/2	C2-G-15	7.3	120/60/1	JB1G-03	6.9	120/60/1
PF-509	R8-G	6.4	120/60/2	C2-G-15	7.6	120/60/1	JB1G-07	6.6	120/60/1
PF-510	R8.1-G	6.7	240/60/1	C2-G-20A	5.5	240/60/1	JB1G-07	4.1	120/60/1
PF-511	R8.2-G	6.6	240/60/1	C2-G-20A	6.5	240/60/1	JB1G-07	4.7	120/60/1
PF-512	R8.3-G	4.9	240/60/3	C2-G-20A	6.6	240/60/1	JB1G-07	5.7	120/60/1
PF-513	R10 9-G	5.9	240/60/3	C2-G-20B	4.9	240/60/1	JB1G-07	6.6	120/60/1
PF-514	R10 9-G	5.5	240/60/3	C2-G-20B	4.7	240/60/1	JB2G-10	4.6	240/60/3
PF-515	R10 9-G	5.3	240/60/3	C2-G-20B	5.1	240/60/1	JB2G-10	5.5	240/60/3
PF-516	R10-G	7.5	240/60/3	C3-G-20	5.8	240/60/3	JB2G-10	6.3	240/60/3
PF-517	R10-G	6.8	240/60/3	C3-G-20	6.5	240/60/3	JB2G-10	5.9	240/60/3
PF-518	R10.1-G	6.4	240/60/3	C3-G-20	7.2	240/60/3	JB2G-10	5.6	240/60/3
PF-519	R10.1-G	7.1	240/60/3	C3-G-25	5.9	240/60/3	JB2G-10	5.9	240/60/3
PF-520	R10.1-G	7.0	240/60/3	C3-G-25	6.4	240/60/3	JB2G-10	6.4	240/60/3
PF-521	R10.1-G	7.7	240/60/3	C3-G-25	7.0	240/60/3	JB2G-20	6.8	240/60/3

\*For gas connection size see Gas/Oil Burner chart.

## GAS/LIGHT OIL BURNERS\*

Boiler Number	Gordon-Platt			Power Flame			Webster		
	Burner Number	Inlet Gas Connection Inches	Standard Motor Voltage	Burner Number	Inlet Gas Connection Inches	Standard Motor Voltage	Burner Number	Inlet Gas Connection Inches	Standard Voltage
PF-504	R6 2-GO	1	120/60/1	C1-GO-12	1	120/60/1	JB1C-03	1 1/4	120/60/1
PF-505	R6 2-GO	1 1/4	120/60/1	C1-GO-12	1	120/60/1	JB1C-03	1 1/4	120/60/1
PF-506	R6 2-GO	1 1/4	120/60/1	C1-GO-12	1	120/60/1	JB1C-03	1 1/4	120/60/1
PF-507	R8-GO	1 1/4	240/60/1	C2-GO-15	1	240/60/1	JB1C-03	1 1/4	120/60/1
PF-508	R8-GO	1 1/2	240/60/1	C2-GO-15	1 1/4	240/60/1	JB1C-03	1 1/2	120/60/1
PF-509	R8-GO	1 1/2	240/60/1	C2-GO-15	1 1/4	240/60/1	JB1C-07	1 1/2	120/60/1
PF-510	R8.1-GO	1 1/2	240/60/1	C2-GO-20A	1 1/4	240/60/1	JB1C-07	2	120/60/1
PF-511	R8.2-GO	1 1/2	240/60/1	C2-GO-20A	1 1/4	240/60/1	JB1C-07	2	120/60/1
PF-512	R8.3-GO	2	240/60/3	C2-GO-20A	1 1/2	240/60/1	JB1C-07	2	120/60/1
PF-513	R10 9-GO	2	240/60/3	C2-GO-20B	2	240/60/1	JB1C-07	2	120/60/1
PF-514	R10 9-GO	2	240/60/3	C2-GO-20B	2	240/60/1	JB2C-10	2	240/60/3
PF-515	R10 9-GO	2	240/60/3	C2-GO-20B	2	240/60/1	JB2C-10	2	240/60/3
PF-516	R10-GO	2	240/60/3	C3-GO-20	2	240/60/3	JB2C-10	2	240/60/3
PF-517	R10-GO	2	240/60/3	C3-GO-20	2	240/60/3	JB2C-10	2 1/2	240/60/3
PF-518	R10.1-GO	2 1/2	240/60/3	C3-GO-20	2	240/60/3	JB2C-10	2 1/2	240/60/3
PF-519	R10.1-GO	2 1/2	240/60/3	C3-GO-25	2	240/60/3	JB2C-10	2 1/2	240/60/3
PF-520	R10.1-GO	2 1/2	240/60/3	C3-GO-25	2	240/60/3	JB2C-20	2 1/2	240/60/3
PF-521	R10.1-GO	2 1/2	240/60/3	C3-GO-25	2	240/60/3	JB2C-20	2 1/2	240/60/3

\*For minimum gas pressure requirements see Gas Burner chart.



BECKETT



GORDON-PIATT



POWERFLAME



WEBSTER

# SPECIFICATIONS



## PF-5 RATINGS



Boiler Number (1)	Boiler H.P.	Gross I = B = R Output MBH	Net I = B = R Rating (2)			I = B = R Burner Capacity		Net Firebox Volume Ft. <sup>3</sup>	Pressure In Firebox (Inches Water Column) (5)	Heating Surface Ft. <sup>2</sup>		Water Content Gal.	
			Steam Sq. Ft.	Steam MBH	Water (3)	Light Oil (4)	Gas MBH			Steam	Water	Steam	Water
PF-504	18.5	620	1938	465	539	5.5	790	8.5	.244	57.45	66.12	58	70
PF-505	23.4	785	2454	589	683	6.9	997	11.1	.244	73.44	85.00	69	84
PF-506	28.4	951	2971	713	827	8.3	1204	13.7	.245	89.43	103.88	81	98
PF-507	33.3	1116	3488	837	970	9.8	1412	16.3	.245	105.42	122.76	92	112
PF-508	38.2	1281	4013	963	1114	11.2	1619	18.9	.246	121.41	141.64	104	127
PF-509	43.2	1446	4583	1100	1257	12.6	1826	21.4	.246	137.40	160.52	115	141
PF-510	48.2	1612	5158	1238	1402	14.0	2033	24.1	.247	153.39	179.40	126	156
PF-511	53.1	1777	5725	1374	1545	15.6	2240	26.8	.247	169.38	198.28	138	170
PF-512	58.1	1942	6283	1508	1689	17.0	2448	29.4	.248	185.37	217.16	149	184
PF-513	63.0	2108	6821	1637	1833	18.4	2655	32.0	.248	201.36	236.04	161	198
PF-514	67.9	2273	7354	1765	1977	19.8	2862	34.6	.249	217.35	254.92	172	212
PF-515	72.9	2438	7888	1893	2120	21.5	3069	37.2	.249	233.34	273.80	184	226
PF-516	77.8	2604	8425	2022	2264	22.5	3276	39.8	.250	249.33	292.68	195	240
PF-517	82.7	2769	8958	2150	2408	24.0	3484	42.4	.250	265.32	311.56	207	255
PF-518	87.7	2934	9492	2278	2551	25.5	3691	45.0	.251	281.31	330.44	218	270
PF-519	92.6	3099	10025	2406	2695	27.0	3898	47.6	.251	297.30	349.32	230	280
PF-520	97.4	3265	10563	2535	2839	28.5	4105	50.2	.252	313.29	368.20	241	298
PF-521	102.5	3430	11096	2663	2983	30.0	4312	52.8	.252	329.28	387.08	253	312

- Suffix "S" indicates steam boiler, "W" indicates water boiler. Suffix "G" indicates gas-fired, "O" oil fired and "GO" for combination gas-oil fired.
- I=B=R net ratings shown are based on piping and pick up allowances which vary from 1.333 to 1.288 for steam and 1.15 for water.
- Net ratings for water, square feet, are based on 170°F average water temperature in system.  
For higher water temperatures, select boiler on basis of I=B=R Net Ratings, MBH.
- The I=B=R burner capacity in GPH is based on oil having a heat value of 140,000 BTU per gallon.

NOTE: Water Working Pressure—Steam 15 PSI W.P.  
Water 50 PSI W.P.  
Water (Optional) 70 PSI W.P.  
(Optional) 30 PSI W.P.

- Boiler ratings are based on 12½% CO<sub>2</sub>, +.10" water column pressure at boiler flue outlet.

I=B=R vent diameter for Boiler No. PF-504 thru PF-508 is 10", for PF-509 - PF-515 is 14" and for PF-516 - PF-521 is 18".

Consult manufacturer for installations having unusual piping and pick up requirements, such as intermittent system operation, extensive piping systems, etc.

Ratings shown above apply at altitudes up to 1000 feet on oil and 2000 feet on gas. For altitudes above those indicated, the ratings should be reduced at the rate of 4% for each 1000 feet above sea level.



Form No. 4256-C-10/94-20Ma  
Printed in U.S.A.  
© 1990 Burnham Corporation, Lancaster, PA