

			Gas Efficiencies				Oil Efficiencies				Outputs								
Model	Inputs			Water		Steam		Water		Steam		Water		Steam			IBR Net Rating		
	Gas Input (MBH)	Oil Input (MBH)	Oil Input (GPH)	Comb. Eff.	Therm. Eff.	Comb. Eff.	Therm. Eff.	Comb. Eff.	Therm. Eff.	Comb. Eff.	Therm. Eff.	Output (MBH)	Output (BHP)	Output (MBH)	Output (BHP)	Output (lb/hr)	Steam (MBH)	Steam (sq ft)	Water (MBH)
4S-100	4184	4032	28.80	85.1%	84.9%	84.3%	83.8%	88.2%	88.00%	87.4%	86.4%	3552	106.1	3506	104.7	3614	2722	11342	3089
4S-125	5230	5068	36.20	85.7%	85.1%	85.0%	84.3%	88.5%	87.8%	87.7%	87.0%	4451	133.0	4409	131.7	4544	3423	14263	3870
4S-150	6277	6062	43.30	85.1%	84.4%	84.4%	83.6%	88.1%	87.4%	87.3%	86.6%	5298	158.3	5248	156.8	5409	4074	16976	4607
4S-175	7323	7084	50.60	85.8%	85.2%	85.0%	84.4%	88.6%	88.0%	87.8%	87.2%	6239	186.4	6181	184.6	6370	4799	19994	5425
4S-200	8369	8120	58.00	86.3%	85.7%	85.5%	84.9%	89.0%	88.4%	88.1%	87.6%	7172	214.3	7105	212.3	7323	5517	22986	6237
4S-250	10461	10122	72.30	85.9%	85.3%	85.1%	84.5%	88.7%	88.1%	87.9%	87.3%	8923	266.6	8840	264.1	9111	6863	28596	7759
4S-300	12553	12166	86.90	86.5%	86.0%	85.8%	85.2%	89.2%	88.7%	88.4%	87.9%	10796	322.5	10695	319.5	11023	8304	34599	9387
4S-350	14645	14196	101.40	86.4%	85.9%	85.6%	85.1%	89.1%	88.6%	88.3%	87.8%	12580	375.8	12463	372.3	12845	9676	40317	10939
4S-400	16738	16226	115.90	86.8%	86.3%	86.1%	85.5%	89.5%	89.0%	88.6%	88.2%	14445	431.5	14311	427.5	14750	11111	46296	12561
4S-500	20922	20286	144.90	86.6%	86.1%	85.8%	85.3%	89.3%	88.8%	88.5%	88.0%	18014	538.1	17846	533.1	18393	13856	57733	15664
4S-600	25106	24346	173.90	87.1%	86.6%	86.4%	85.9%	89.7%	89.3%	88.9%	88.4%	21742	649.5	21566	644.2	22227	16744	69766	18906
4S-700	29291	28364	202.60	86.8%	86.3%	86.0%	85.5%	89.5%	89.1%	88.7%	88.2%	25278	755.1	25044	748.1	25811	19444	81016	21981
4S-800	33475	32466	231.90	87.2%	86.7%	86.4%	86.0%	89.8%	89.4%	88.9%	88.5%	29023	867.0	28789	860.0	29670	22351	93130	25237