


5022 16" 10"	5021	BOILER "A" "DA" "DB" "Dc" "F" "G" "J" "K" "L" "M" "N"		
16"	16"	"A"		
10"	9"	"Da"		
10"	10"	"D _B "		
12"	12"	"Dc"		
12" 325%" 4034" 277%" 3234" 121" 325%" 491%"	12" 297%" 4034" 277%" 273%" 115½" 325%" 491%"	"F"		
40¾"	40¾"	"G"		
27%"	27%"	"J"		
32¾"	27%"	"K"		
121"	115½"	"L"		
32%"	32%"	"M"		
491/8"	491/8"	"N"		
3"	3"	(1)	RISER	
4"	4"	(2)	HEADER	
5"	5,"	(3)	HEADER	
6"	6"	(4)	HEADER	
2½"	2½"	(5)	EQUALIZER	
2"	2"	6	RETURN	
1½"	1½"	(7)	MAKE-UP WATER	



PLAN VIEW





ALTERNATE PIPING DETAIL RETURN CONNECTION HARTFORD LOOP

- 1.) ALL PIPING IS SCHEDULE 40.
 2.) PIPING AT REAR OF BOILER SHOULD NOT INTERFERE WITH REMOVAL OF UPPER REAR PANELS FOR ACCESS TO FLUEWAYS FOR CLEANING. THESE SCHEMATIC DRAWINGS ARE INTENDED SOLELY TO SHOW RECOMMENDED TAPPING LOCATIONS AND GENERAL PIPING ARRANGEMENTS. ACTUAL PIPING DETAILS SHOULD BE DESIGNED IN ACCORDEANCE WITH STANDARD ENGINEERING PRACTICES.
 3.) (3) SUPPLY CONNECTIONS AND (2) RETURN CONNECTIONS FOR SIZE 5021 AND 5022.

	7		
	ין ון	COMPON	THIS D
,		PER SIZING, VENTS ARE TH	THIS DRAWING DEPIC
NICS DIVISION PA 17804-3079	9	SELECTION, LO)TS A GENERA ICLUSIVE) USE
MINIMUM	DRAWING TITL	ILITY OF THE	THIS DRAWING DEPICTS A GENERAL LAYOUT OF THE COMPONENTS NECESSARILY ALL INCLUSIVE) USED FOR A TYPICAL APPLICATION.
PIPING RECON SINGLE/STE/ 5021 AND 50	'n	NSTALLATION DESIGNER OR	THE COMPONI
MMEND 322		OF AL	٠,
ATIONS		LLER.	ĬŜ
AE-5B-0167	DRAWING NO.	DWG. DATE 10/05/00	PART NO.(S)
	MINIMUM PIPING RECOMMENDATIONS HYDRONICS DIVISION HYDRONICS DIVISION SINGLE/STEAM 5021 AND 5022	DRAWING TITLE DRAWING TITLE MINIMUM PIPING RECOMMENDATIONS SINGLE/STEAM SO21 AND 5022	TO THE RESPONSIBILITY OF THE DESIGNER OR INSTALLER. DRAWING TITLE DRAWING TITLE MINIMUM PIPING RECOMMENDATIONS SINGLE/STEM LINCASTER, PA. 17804–3079 DRAWING TITLE DRAWING TITLE MINIMUM PIPING RECOMMENDATIONS SINGLE/STEM 5021 AND 5022