



NOTES:

1. TYPICAL POWER FLAME 'CR' BURNER LENGTH SHOWN. EXACT BURNER DIMENSIONS MAY VARY.
2. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
3. SECOND SUPPLY NOT NEEDED FOR 40°F TEMPERATURE RISE APPLICATIONS.

	APPROVED	DRAWN	REV. A2	6/23/22	[FRONT VIEW] 3" RETURN: (2 PLACES - REAR ONLY)
		EJL			(WAS) (4 PLACES). SEE EN. #93-54-15003.
	APPROVED	DRAWN	REV. A	7/22/21	ADDED PACKAGED BASE & BLOCK BASE LAYERS.
		RAR			

DIMENSIONS IN INCHES, FRACTIONAL TOLERANCES ±1/32", ANGULAR TOLERANCES ±1°, UNLESS OTHERWISE NOTED.			SUPERSEDES		DWG. DATE 12/22/08
BURNHAM Commercial Boilers			DRAWING TITLE		DRAWING NO.
			DIMENSIONAL DRAWING V1119 WATER BOILER 20°F OR 40°F TEMPERATURE RISE		TS-93-79-B
DRAWN EAB	CHECKED	DESIGNED	APPROVED MZ	RELEASED	DWG. SCALE 3/64"=1"
			REV. LEVEL A2		